

Constant Voltage Mode

CVL Range	0.000 ~ 60.00	V
CVL Program Resolution*2	16.67	mV
CVL Program Accuracy*2	0.10% ± 0.060	V
CVL Readback Resolution	16.67	mV
CVL Readback Accuracy	0.20% ± 0.060	V
CVL Slew Rate Range	0.220 ~ 60.00	V/ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	

Constant Current Mode

CCM Range	0.000 ~ 120.0	A
CCL Range	0.000 ~ 12.00	A
Minimum Voltage at Imax	1.000	V
Transient Time	100.0	us
CCM Program Resolution*2	33.33	mA
CCL Program Resolution*2	3.333	mA
CCM Program Accuracy*2	0.10% ± 0.120	A
CCL Program Accuracy*2	0.10% ± 0.120	A
CCM Readback Resolution	33.33	mA
CCL Readback Resolution	3.333	mA
CCM Readback Accuracy	0.20% ± 0.120	A
CCL Readback Accuracy	0.20% ± 0.120	A
CCM Slew Rate Range	0.0044 ~ 1.200	A/us
CCL Slew Rate Range	0.00044 ~ 0.120	A/us
Temperature Coefficient	100 ppm / °C of Rated Current	

External Mode

Analog Program	0~10 Volts Input yields 0~selected full scaled loading in CC mode		
Accuracy	Same As Internal ± 0.1% Rating		
Input Impedance	147 kΩ	±	2 %
Monitor output Signal	0~10 Volts output for 0~full scaled current		
VMON Accuracy	0.10%	±	0.060 V
IMON Accuracy	0.10%	±	0.120 A

Programmable Protection

Power(OPP)		
Range	0.833 ~ 330.0	W
Resolution	0.083	W
Accuracy	1.00% ± 1.667	W
Voltage(OVP)		
Range	0.167 ~ 66.00	V
Resolution	16.67	mV
Accuracy	0.20% ± 0.167	V
Current(OCP)		
Range	0.333 ~ 132.0	A
Resolution	33.33	mA
Accuracy	0.20% ± 0.333	A

Constant Power Mode

CPM Range	0.000 ~ 300.0	W
CPL Range	0.000 ~ 30.00	W
	@ lin ≤ 12.00	A
CPM Resolution*2	0.083	W
CPL Resolution*2	0.0083	W
CPM Accuracy*2	1.0% ± 2.000	+
	0.250 × 30.00 — Vin	W
CPL Accuracy*2	1.0% ± 0.400	+
	0.050 × 30.00 — Vin	W
CPM / L Slew Rate Range	Same As CC Mode	
Temperature Coefficient	300 ppm / °C of Rated Power	

Constant Resistance Mode

CRH Range	5.000 ~ 900.0	Ω
	@ lin ≤ 12.00	A
CRM Range	0.500 ~ 5.000	Ω
CRL Range	0.008 ~ 0.500	Ω
CRH Resolution*2	0.0667	mS
CRM Resolution*2	0.667	mS
CRL Resolution*2	0.167	mΩ
CRH Accuracy*2	1.00% ± 1.600	mS
	@lin > 0.120	A
	& Vin > 15.00	V
CRM Accuracy*2	1.00% ± 4.000	mS
	@lin > 1.200	A
	& Vin > 6.000	V
CRL Accuracy*2	1.00% ± 1.000	mΩ
	@lin > 12.00	A
	& Vin > 0.060	V
CRM / CRH Slew Rate Range	Same As CC Mode	
CRL Slew Rate Range	Same As CV Mode	
CRM / H Temperature Coefficient	300 ppm / °C of Minimum Resistance	
CRL Temperature Coefficient	300 ppm / °C of Maximum Resistance	

General

Transient Mode		
Frequency Range	0.100 ~ 20,000	Hz
Accuracy	0.2%	
Duty Range	1.000 ~ 99.0	%
Accuracy	0.2%	
Transient Time Accuracy	15.0% ± 50% of Minimum Time	
Remote Interface	GPIO / RS-232	
Derating for higher temperatures	(-)2.25% Rated Power / °C	
AC Input	115 / 230 Vac 50 / 60 Hz	
Power Consumption	35 VA	
Operating Temperature	5 °C ~ 40 °C	
Dimension	21.85"(L)x8.27"(W)x7.57"(H)	
Weight	33 lbs 15.0 kg	
Approx.Shipping Weight	48 lbs 21.8 kg	

*1 All Mode Specification measure by 25 °C room temperature unless otherwise specified
 *2 Transient Mode Specification must be x2
 AMREL reserves the right to change limits, test conditions, and dimensions without notice



PEL300-60-120 (60V,120A,300W) OPERATIONAL CURVE

