

Constant Voltage Mode

CVL Range	0.000 ~ 120.0	V
CVL Program Resolution*2	33.33	mV
CVL Program Accuracy*2	0.10% ± 0.120	V
CVL Readback Resolution	33.33	mV
CVL Readback Accuracy	0.20% ± 0.120	V
CVL Slew Rate Range	0.439 ~ 120.0	V/ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	

Constant Current Mode

CCM Range	0.000 ~ 120.0	A
CCL Range	0.000 ~ 12.00	A
Minimum Voltage at Imax	1.000	V
Transient Time	100.0	us
CCM Program Resolution*2	33.33	mA
CCL Program Resolution*2	3.333	mA
CCM Program Accuracy*2	0.10% ± 0.120	A
CCL Program Accuracy*2	0.10% ± 0.120	A
CCM Readback Resolution	33.33	mA
CCL Readback Resolution	3.333	mA
CCM Readback Accuracy	0.20% ± 0.120	A
CCL Readback Accuracy	0.20% ± 0.120	A
CCM Slew Rate Range	0.0044 ~ 1.200	A/us
CCL Slew Rate Range	0.00044 ~ 0.120	A/us
Temperature Coefficient	100 ppm / °C of Rated Current	

External Mode

Analog Program	0~10 Volts Input yields 0~selected full scaled loading in CC mode		
Accuracy	Same As Internal ± 0.1% Rating		
Input Impedance	147 kΩ	±	2 %
Monitor output Signal	0~10 Volts output for 0~full scaled current		
VMON Accuracy	0.10%	±	0.120 V
IMON Accuracy	0.10%	±	0.120 A

Programmable Protection

Power(OPP)		
Range	1.667 ~ 660.0	W
Resolution	0.167	W
Accuracy	1.00% ± 3.333	W
Voltage(OVP)		
Range	0.333 ~ 132.0	V
Resolution	33.33	mV
Accuracy	0.20% ± 0.333	V
Current(OCP)		
Range	0.333 ~ 132.0	A
Resolution	33.33	mA
Accuracy	0.20% ± 0.333	A

Constant Power Mode

CPM Range	0.000 ~ 600.0	W
CPL Range	0.000 ~ 60.00	W
	@ lin ≤ 12.00	A
CPM Resolution*2	0.167	W
CPL Resolution*2	0.0167	W
CPM Accuracy*2	1.0% ± 4.00	+
	0.250 × 60.0	— Vin W
CPL Accuracy*2	1.0% ± 0.800	+
	0.050 × 60.0	— Vin W
CPM / L Slew Rate Range	Same As CC Mode	
Temperature Coefficient	300 ppm / °C of Rated Power	

Constant Resistance Mode

CRH Range	10.00 ~ 1,800	Ω
	@ lin ≤ 12.00	A
CRM Range	1.000 ~ 10.00	Ω
CRL Range	0.008 ~ 1.000	Ω
CRH Resolution*2	0.0333	mS
CRM Resolution*2	0.333	mS
CRL Resolution*2	0.333	mΩ
CRH Accuracy*2	1.00% ± 0.800	mS
	@lin > 0.120	A
	& Vin > 30.00	V
CRM Accuracy*2	1.00% ± 2.000	mS
	@lin > 1.200	A
	& Vin > 12.00	V
CRL Accuracy*2	1.00% ± 2.000	mΩ
	@lin > 12.00	A
	& Vin > 0.120	V
CRM / CRH Slew Rate Range	Same As CC Mode	
CRL Slew Rate Range	Same As CV Mode	
CRM / H Temperature Coefficient	300 ppm / °C of Minimum Resistance	
CRL Temperature Coefficient	300 ppm / °C of Maximum Resistance	

General

Transient Mode		
Frequency Range	0.100 ~ 20,000	Hz
Accuracy	0.2%	
Duty Range	1.000 ~ 99.0	%
Accuracy	0.2%	
Transient Time Accuracy	15.0% ± 50% of Minimum Time	
Remote Interface	GPIO / RS-232	
Derating for higher temperatures	(-)2.25% Rated Power / °C	
AC Input	115 / 230 Vac 50 / 60 Hz	
Power Consumption	35 VA	
Operating Temperature	5 °C ~ 40 °C	
Dimension	22.44"(L)x12.52"(W)x7.57"(H)	
Weight	52 lbs 23.6 kg	
Approx.Shipping Weight	67 lbs 30.4 kg	

*1 All Mode Specification measure by 25 °C room temperature unless otherwise specified

*2 Transient Mode Specification must be x2

AMREL reserves the right to change limits, test conditions, and dimensions without notice



PEL600-120-120 (120V,120A,600W) OPERATIONAL CURVE

