

## Constant Voltage Mode

CVH Range	0.000 ~ 400.0	V
CVM Range	0.000 ~ 200.0	V
CVL Range	0.000 ~ 40.00	V
Transient Time Range		
Fast Band(Default,Osc1)	0.250 ~ 25.59	ms
Slow Band(Osc2,Osc3)	0.250 ~ 255.9	ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	

Program	CV Resolution*2	1/16000 of Rated Voltage
	CVH Accuracy*2	0.05% ± 0.400 V
	CVM Accuracy*2	0.05% ± 0.400 V
	CVL Accuracy*2	0.05% ± 0.400 V

Display	CVH Resolution	1/16000 of Rated Voltage
	CVH Accuracy	0.05% ± 0.400 V
	CVM Accuracy	0.05% ± 0.400 V
	CCL Accuracy	0.05% ± 0.400 V

## Constant Current Mode

CCH Range	0.000 ~ 30.00	A
CCM Range	0.000 ~ 15.00	A
CCL Range	0.000 ~ 3.000	A
Transient Time Range		
Fast Band(Default,Osc1)	0.025 ~ 25.59	ms
Slow Band(Osc2,Osc3)	0.250 ~ 255.9	ms
Minimum Voltage(I <sub>Max</sub> )	1.800	V
Temperature Coefficient	100 ppm / °C of Rated Current	

Program	CC Resolution*2	1/16000 of Rated Current
	CCH Accuracy*2	0.05% ± 0.030 A
	CCM Accuracy*2	0.05% ± 0.030 A
	CCL Accuracy*2	0.05% ± 0.030 A

Display	CC Resolution	1/16000 of Rated Current
	CCH Accuracy	0.05% ± 0.030 A
	CCM Accuracy	0.05% ± 0.030 A
	CCL Accuracy	0.05% ± 0.030 A

## Programmable Protection

Power(OPP)		
Range	0.825 ~ 660.0	W
Resolution	0.083	W
Accuracy	0.50% ± 1.650	W
Voltage(OVP)		
Range	0.263 ~ 420.0	V
Resolution	0.026	V
Accuracy	0.20% ± 0.525	V
Current(OCP)		
Range	0.020 ~ 31.50	A
Resolution	0.002	A
Accuracy	0.20% ± 0.039	A
Under Voltage Lockout(UVL)		
Mode	Input On / Continuous	
Range	0.300 ~ 400.0	V
Resolution	0.100	V
Accuracy	2.50% ± 0.500	V
Anti-Oscillation	Default / Osc1 / Osc2 / Osc3 / Disable	

## Protection

Over Power Protection(OP)	660.0 ± 12.57	W
Over Voltage Protection(OV)	420.0 ± 8.000	V
Over Current Protection(OC)	33.00 ± 0.314	A
Over Temperature Protection(OTP)	90.00 ± 5.000	°C
Reverse Maximum Current(RCP)	33.00	A
Short Maximum Current	30.60	A
Remote Inhibit(RI)	Short	
Fault Indicator	SPDT Relay (30Vdc/0.5A or 125Vac/0.25A)	

## Dielectric Strength

Primary Circuit To Chassis	1500 Vac for 1 min
Primary Circuit To Load Terminal	1500 Vac for 1 min
Load Terminal To Chassis	1500 Vdc for 1 min

## Constant Power Mode

CPH Range	0.000 ~ 600.0	W
CPM Range	0.000 ~ 300.0	W
	@ lin ≤ 15.00	A
CPL Range	0.000 ~ 60.00	W
	@ lin ≤ 3.000	A
Transient Time Range	Same As CC Mode	
Temperature Coefficient	300 ppm / °C of Rated Power	

Program	CP Resolution*2	1/16000 of Rated Power
	CPH Accuracy*2	1.00% ± 3.000 W
		@lin > 1.500 A
		& Vin > 40.00 V
	CPM Accuracy*2	1.00% ± 3.000 W
		@lin > 0.300 A
		& Vin > 40.00 V
	CPL Accuracy*2	1.00% ± 3.000 W
		@lin > 0.030 A
		& Vin > 80.00 V

## Constant Resistance Mode

CRH Range	133.3 ~ 6,667	Ω
	@ lin ≤ 3.000	A
CRM Range	13.33 ~ 3,333	Ω
CRL Range	0.0600 ~ 13.33	Ω

Transient Time Range	Same As CC Mode
CRM / CRH	Same As CV Mode
CRL	

Temperature Coefficient	
CRM / H	300 ppm / °C of Minimum Resistance
CRL	300 ppm / °C of Maximum Resistance

Program	CR Resolution*2	1/16000 Of Rated Value
	CRH Accuracy*2	1.00% ± 0.038 mS
		@lin > 0.030 A
		& Vin > 80.00 V
	CRM Accuracy*2	1.00% ± 0.150 mS
		@lin > 0.300 A
		& Vin > 40.00 V
	CRL Accuracy*2	1.00% ± 13.33 mΩ
		@lin > 3.000 A
		& Vin > 0.400 V

## External Programming Mode

Analog Program	0~10 Volts Input yields
	0~selected full scaled loading in all modes
Accuracy	Same As Internal ± 0.1% Rating
Input Impedance	400 kΩ ± 1 %
BandWidth(-3dB)	Limited By Internal Transient Time
Monitor output Signal	0~10 Volts output for 0~full scaled Value
VMON Accuracy	0.10% ± 0.400 V
IMON Accuracy	0.10% ± 0.030 A
Transient Mode	
Frequency Range	0.100 ~ 20,000 Hz
Accuracy	0.1%
Duty Range	1.000 ~ 100.0 %
Accuracy	0.1%
Transient Time Accuracy	10.0% ± 50% of Minimum Time
Remote Interface	GPIOB / RS-232 / ETHERNET / USB

## General

Derating for higher temperatures (-)1.67% Rated Power / °C

AC Input	95~240 Vac 48~62 Hz
Power Consumption	80 VA
Operating Temperature	5 °C ~ 40 °C
Dimension	21"(L)x17"(W)x1.75"(H)

Weight 23 lbs 10.4 kg

Approx.Shipping Weight 38 lbs 17.2 kg

LPL600-400-30 (400V,30A,600W) OPERATIONAL CURVE

