

Constant Voltage Mode

CVH Range	0.000 ~ 120.0	V
CVM Range	0.000 ~ 60.00	V
CVL Range	0.000 ~ 12.00	V
Transient Time Range		
Fast Band(Default,Osc1)	0.500 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	

Program	CV Resolution*2	1/16000 of Rated Voltage
	CVH Accuracy*2	0.05% ± 0.120 V
	CVM Accuracy*2	0.05% ± 0.120 V
	CVL Accuracy*2	0.05% ± 0.120 V

Display	CVH Resolution	1/16000 of Rated Voltage
	CVH Accuracy	0.05% ± 0.120 V
	CVM Accuracy	0.05% ± 0.120 V
	CCL Accuracy	0.05% ± 0.120 V

Constant Current Mode

CCH Range	0.000 ~ 150.0	A
CCM Range	0.000 ~ 75.00	A
CCL Range	0.000 ~ 15.00	A
Transient Time Range		
Fast Band(Default,Osc1)	0.050 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Minimum Voltage(I _{Max})	1.200	V
Temperature Coefficient	100 ppm / °C of Rated Current	

Program	CC Resolution*2	1/16000 of Rated Current
	CCH Accuracy*2	0.05% ± 0.150 A
	CCM Accuracy*2	0.05% ± 0.150 A
	CCL Accuracy*2	0.05% ± 0.150 A

Display	CC Resolution	1/16000 of Rated Current
	CCH Accuracy	0.05% ± 0.150 A
	CCM Accuracy	0.05% ± 0.150 A
	CCL Accuracy	0.05% ± 0.150 A

Programmable Protection

Power(OPP)		
Range	1.100 ~ 880.0	W
Resolution	0.110	W
Accuracy	0.50% ± 2.200	W
Voltage(OVP)		
Range	0.079 ~ 126.0	V
Resolution	0.008	V
Accuracy	0.20% ± 0.158	V
Current(OCP)		
Range	0.098 ~ 157.5	A
Resolution	0.010	A
Accuracy	0.20% ± 0.197	A
Under Voltage Lockout(UVL)		
Mode	Input On / Continuous	
Range	0.090 ~ 120.0	V
Resolution	0.030	V
Accuracy	2.50% ± 0.150	V
Anti-Oscillation	Default / Osc1 / Osc2 / Osc3 / Disable	

Protection

Over Power Protection(OP)	880.0 ± 16.76	W
Over Voltage Protection(OV)	126.0 ± 2.400	V
Over Current Protection(OC)	165.0 ± 1.571	A
Over Temperature Protection(OTP)	90.00 ± 5.000	°C
Reverse Maximum Current(RCP)	165.0	A
Short Maximum Current	153.0	A
Remote Inhibit(RI)	Short	
Fault Indicator	SPDT Relay (30Vdc/0.5A or 125Vac/0.25A)	

Dielectric Strength

Primary Circuit To Chassis	1500 Vac for 1 min
Primary Circuit To Load Terminal	1500 Vac for 1 min
Load Terminal To Chassis	1500 Vdc for 1 min

Constant Power Mode

CPH Range	0.000 ~ 800.0	W
CPM Range	0.000 ~ 400.0	W
@ lin	≤ 75.00	A
CPL Range	0.000 ~ 80.00	W
@ lin	≤ 15.00	A
Transient Time Range	Same As CC Mode	
Temperature Coefficient	300 ppm / °C of Rated Power	

Program	CP Resolution*2	1/16000 of Rated Power
	CPH Accuracy*2	1.00% ± 4.000 W
	@lin	> 7.500 A
	& Vin	> 12.00 V
	CPM Accuracy*2	1.00% ± 4.000 W
	@lin	> 1.500 A
	& Vin	> 12.00 V
	CPL Accuracy*2	1.00% ± 4.000 W
	@lin	> 0.150 A
	& Vin	> 24.00 V

Constant Resistance Mode

CRH Range	8.000 ~ 400.0	Ω
@ lin	≤ 15.00	A
CRM Range	0.8000 ~ 200.0	Ω
CRL Range	0.0080 ~ 0.8000	Ω

Transient Time Range	Same As CC Mode
CRM / CRH	Same As CV Mode
CRL	

Temperature Coefficient	
CRM / H	300 ppm / °C of Minimum Resistance
CRL	300 ppm / °C of Maximum Resistance

Program	CR Resolution*2	1/16000 Of Rated Value
	CRH Accuracy*2	1.00% ± 0.625 mS
	@lin	> 0.150 A
	& Vin	> 24.00 V
	CRM Accuracy*2	1.00% ± 2.500 mS
	@lin	> 1.500 A
	& Vin	> 12.00 V
	CRL Accuracy*2	1.00% ± 0.800 mΩ
	@lin	> 15.00 A
	& Vin	> 0.120 V

External Programming Mode

Analog Program	0~10 Volts Input yields
	0~selected full scaled loading in all modes
Accuracy	Same As Internal ± 0.1% Rating
Input Impedance	400 kΩ ± 1 %
BandWidth(-3dB)	Limited By Internal Transient Time
Monitor output Signal	0~10 Volts output for 0~full scaled Value
VMON Accuracy	0.10% ± 0.120 V
IMON Accuracy	0.10% ± 0.150 A
Transient Mode	
Frequency Range	0.100 ~ 10,000 Hz
Accuracy	0.1%
Duty Range	1.000 ~ 100.0 %
Accuracy	0.1%
Transient Time Accuracy	10.0% ± 50% of Minimum Time
Remote Interface	GPIOB / RS-232 / ETHERNET / USB

General

Derating for higher temperatures (-)1.67% Rated Power / °C

AC Input	95~240 Vac 48~62 Hz
Power Consumption	100 VA
Operating Temperature	5 °C ~ 40 °C
Dimension	19.5"(L)x17"(W)x3.5"(H)

Weight 28 lbs 12.7 kg

Approx.Shipping Weight 54 lbs 24.5 kg



PLA800-120-150 (120V,150A,800W) OPERATIONAL CURVE

