

Constant Voltage Mode

| | | |
|-------------------------|-------------------------------|----|
| CVH Range | 0.000 ~ 60.00 | V |
| CVM Range | 0.000 ~ 30.00 | V |
| CVL Range | 0.000 ~ 6.000 | V |
| Transient Time Range | | |
| Fast Band(Default,Osc1) | 0.500 ~ 51.19 | ms |
| Slow Band(Osc2,Osc3) | 0.500 ~ 511.9 | ms |
| Temperature Coefficient | 100 ppm / °C of Rated Voltage | |

| | | |
|---------|-----------------|--------------------------|
| Program | CV Resolution*2 | 1/16000 of Rated Voltage |
| | CVH Accuracy*2 | 0.05% ± 0.060 V |
| | CVM Accuracy*2 | 0.05% ± 0.060 V |
| | CVL Accuracy*2 | 0.05% ± 0.060 V |

| | | |
|---------|----------------|--------------------------|
| Display | CVH Resolution | 1/16000 of Rated Voltage |
| | CVH Accuracy | 0.05% ± 0.060 V |
| | CVM Accuracy | 0.05% ± 0.060 V |
| | CCL Accuracy | 0.05% ± 0.060 V |

Constant Current Mode

| | | |
|------------------------------------|-------------------------------|----|
| CCH Range | 0.000 ~ 1,500 | A |
| CCM Range | 0.000 ~ 750.0 | A |
| CCL Range | 0.000 ~ 150.0 | A |
| Transient Time Range | | |
| Fast Band(Default,Osc1) | 0.050 ~ 51.19 | ms |
| Slow Band(Osc2,Osc3) | 0.500 ~ 511.9 | ms |
| Minimum Voltage(I _{Max}) | 0.600 | V |
| Temperature Coefficient | 100 ppm / °C of Rated Current | |

| | | |
|---------|-----------------|--------------------------|
| Program | CC Resolution*2 | 1/16000 of Rated Current |
| | CCH Accuracy*2 | 0.05% ± 1.500 A |
| | CCM Accuracy*2 | 0.05% ± 1.500 A |
| | CCL Accuracy*2 | 0.05% ± 1.500 A |

| | | |
|---------|---------------|--------------------------|
| Display | CC Resolution | 1/16000 of Rated Current |
| | CCH Accuracy | 0.05% ± 1.500 A |
| | CCM Accuracy | 0.05% ± 1.500 A |
| | CCL Accuracy | 0.05% ± 1.500 A |

Programmable Protection

| | | |
|----------------------------|--|---|
| Power(OPP) | | |
| Range | 10.31 ~ 8,250 | W |
| Resolution | 1.031 | W |
| Accuracy | 0.50% ± 20.63 | W |
| Voltage(OVP) | | |
| Range | 0.039 ~ 63.00 | V |
| Resolution | 0.004 | V |
| Accuracy | 0.20% ± 0.079 | V |
| Current(OCP) | | |
| Range | 0.984 ~ 1,575 | A |
| Resolution | 0.098 | A |
| Accuracy | 0.20% ± 1.969 | A |
| Under Voltage Lockout(UVL) | | |
| Mode | Input On / Continuous | |
| Range | 0.045 ~ 60.00 | V |
| Resolution | 0.015 | V |
| Accuracy | 2.50% ± 0.075 | V |
| Anti-Oscillation | Default / Osc1 / Osc2 / Osc3 / Disable | |

Protection

| | | |
|----------------------------------|---|----|
| Over Power Protection(OP) | 8,250 ± 157.1 | W |
| Over Voltage Protection(OV) | 63.00 ± 1.200 | V |
| Over Current Protection(OC) | 1,650 ± 15.71 | A |
| Over Temperature Protection(OTP) | 90.00 ± 5.000 | °C |
| Reverse Maximum Current(RCP) | 1,650 | A |
| Short Maximum Current | 1,530 | A |
| Remote Inhibit(RI) | Short | |
| Fault Indicator | SPDT Relay (30Vdc/0.5A or 125Vac/0.25A) | |

Dielectric Strength

| | |
|----------------------------------|--------------------|
| Primary Circuit To Chassis | 1500 Vac for 1 min |
| Primary Circuit To Load Terminal | 1500 Vac for 1 min |
| Load Terminal To Chassis | 1500 Vdc for 1 min |

Constant Power Mode

| | | |
|-------------------------|-----------------------------|---|
| CPH Range | 0.000 ~ 7,500 | W |
| CPM Range | 0.000 ~ 3,750 | W |
| | @ lin ≤ 750.0 | A |
| CPL Range | 0.000 ~ 750.0 | W |
| | @ lin ≤ 150.0 | A |
| Transient Time Range | Same As CC Mode | |
| Temperature Coefficient | 300 ppm / °C of Rated Power | |

| | | |
|---------|-----------------|------------------------|
| Program | CP Resolution*2 | 1/16000 of Rated Power |
| | CPH Accuracy*2 | 1.00% ± 37.50 W |
| | | @lin > 75.00 A |
| | | & Vin > 6.000 V |
| | CPM Accuracy*2 | 1.00% ± 37.50 W |
| | | @lin > 15.00 A |
| | | & Vin > 6.000 V |
| | CPL Accuracy*2 | 1.00% ± 37.50 W |
| | | @lin > 1.500 A |
| | | & Vin > 12.00 V |

Constant Resistance Mode

| | | |
|-----------|-----------------|---|
| CRH Range | 0.4000 ~ 20.00 | Ω |
| | @ lin ≤ 150.0 | A |
| CRM Range | 0.0400 ~ 10.00 | Ω |
| CRL Range | 0.0004 ~ 0.0400 | Ω |

| | |
|----------------------|-----------------|
| Transient Time Range | Same As CC Mode |
| CRM / CRH | Same As CV Mode |
| CRL | |

| | |
|-------------------------|------------------------------------|
| Temperature Coefficient | |
| CRM / H | 300 ppm / °C of Minimum Resistance |
| CRL | 300 ppm / °C of Maximum Resistance |

| | | |
|---------|-----------------|------------------------|
| Program | CR Resolution*2 | 1/16000 Of Rated Value |
| | CRH Accuracy*2 | 1.00% ± 12.50 mS |
| | | @lin > 1.500 A |
| | | & Vin > 12.00 V |
| | CRM Accuracy*2 | 1.00% ± 50.00 mS |
| | | @lin > 15.00 A |
| | | & Vin > 6.000 V |
| | CRL Accuracy*2 | 1.00% ± 0.040 mΩ |
| | | @lin > 150.0 A |
| | | & Vin > 0.060 V |

External Programming Mode

| | |
|-------------------------|---|
| Analog Program | 0~10 Volts Input yields |
| | 0~selected full scaled loading in all modes |
| Accuracy | Same As Internal ± 0.1% Rating |
| Input Impedance | 400 kΩ ± 1 % |
| BandWidth(-3dB) | Limited By Internal Transient Time |
| Monitor output Signal | 0~10 Volts output for 0~full scaled Value |
| VMON Accuracy | 0.10% ± 0.060 V |
| IMON Accuracy | 0.10% ± 1.500 A |
| Transient Mode | |
| Frequency Range | 0.100 ~ 10,000 Hz |
| Accuracy | 0.1% |
| Duty Range | 1.000 ~ 100.0 % |
| Accuracy | 0.1% |
| Transient Time Accuracy | 10.0% ± 50% of Minimum Time |
| Remote Interface | GPIOB / RS-232 / ETHERNET / USB |

General

Derating for higher temperatures (-)1.67% Rated Power / °C

| | |
|-----------------------|--------------------------|
| AC Input | 95~240 Vac 48~62 Hz |
| Power Consumption | 280 VA |
| Operating Temperature | 5 °C ~ 40 °C |
| Dimension | 24.5"(L)x17"(W)x10.5"(H) |

Weight 135 lbs 61.2 kg

Approx.Shipping Weight 195 lbs 88.5 kg

PLA7.5K-60-1500 (60V,1500A,7.5KW) OPERATIONAL CURVE

